ZCS-KDCA1-6N/EX6 Security Camera Docking Station





EX6

6N

Features -----

- High Performance 13.3" color LCD with resolution of 1920 × 1080
- Supports up to 24 units of body worn camera
- Supports up to 24TB storage

Easy to Use


- Wall-mounted and desktop designed, easy to install Modular design, easy to upgrade system capacity Plug and play, auto charging and data transmission
- Touch screen operation

Abundant Functions and Features

- Record searching and playback
- _ Auto lock after device pluged in
- Use the password to unlock device Priority slot for high speed data transmission
- -Built-in battery protection for sudden power-off / shut down -

Dimensions ------





ģ

Specifications -----

	ZCS-KDCA1-6N/EX6
System	
Operating System	Windows10
Processor	Intel N3710
Application System	Data Docking Station Management Software
RAM	4GB
User Management	Admin / User
Log Management	User login / User operation / Alarm / Update
Display	User login / User Operation / Mann / Opdate
Size	13.3"
Resolution	
	1920 x 1080
Touch Screen	Supported
Search & Playback	
File Type	Video, Audio, Pic, Log
Search Mode	Duration filter / Tag
Playback Resolution	1 x 1080p@30fp
Functions	Querying, Viewing, Downloading, Removing
Slot	······································
0101	ZCS-KDCA1-6: 6 Slots by default, supports 6 units of Body Worn Camera
Default Slot	Supports up to 3 extended modules (6 slots per module)
	Applies to DSJ-U1-W
	ZCS-KDCA1-6N: 6 Slots by default, supports 6 units of Body Worn Camera
	Supports up to 3 extended modules (6 slots per module)
	Applies to DSJ-U1-WN
Extended Module	ZCS-KDCA1-EX6: Extended module of ZCS-KDCA1-6, 6 slots per module, supports
	6 units of Body Worn Cameras)
	Applies to DSJ-U1-
	ZCS-KDCA1-EX6N: Extended module of ZCS-KDCA1-6N, 6 slots per module,
	supports 6 units of Body Worn Cameras)
	Applies to DSJ-U1-WN
Slot Funtions	Battery charging, Data transmission, Lock, Priority slot, Automatic upgrade, Time
	correction
Data Loading Speed	Full load: up to 4.6MB/s per slot
• •	For priority slot: up to 15MB/s
Alarm	
System Alarm Triggers	No disk / Insufficient recording space / Network disconnected
Alarm Events	Buzzer / Alarm text
Storage	
	3 x 3.5" hard disk drawer (1 x 4TB Hard disk included)
Max. Internal HDDs	Max. 24TB (up to 8TB/each)
RAID	RAID 1
Interfaces	10101
Ethernet	1 a Circleite actual and DME interface
	1 x Gigabite network port, RJ45 interface
Audio Out	Build-in speaker
Point lock	1 x Point lock (Unlock all devices at the same time bye key)
	1 x USB 2.0: for extended device
USB	2 x Mini USB: for thirdparty device charging
	2 x Micro USB: for thirdparty device charging
Environmental	
Operating Temperature	-10°C ~ 55°C / 14°F ~ 131°F
Operating Humidity	10% ~ 95%
Electrical	170.10 20.10
	100 ~ 240V AC, 50 ~ 60Hz
Power	
	ZCS-KDCA1-6/6N: Max. 105W
Power Consumption	ZCS-KDCA1-6/6N + 1 x ZCS-KDCA1-EX6/6N: Max. 135W
	ZCS-KDCA1-6/6N + 2 x ZCS-KDCA1-EX6/6N: Max. 165W
	ZCS-KDCA1-6/6N + 3 x ZCS-KDCA1-EX6/6N: Max. 195W
Emergency Power	Built-in battery: 2150mAh
Mechanical	punchi battery, 2130mpm
rechanical	ZCC KDCA1 C/CN: 10 2K- / 22 7lb (UDD not included)
Weight	ZCS-KDCA1-6/6N: 10.3Kg / 22.7lb (HDD not included)
	ZCS-KDCA1-EX6/6N: 3.68Kg/8.11lb
Dimensions	ZCS-KDCA1-6/6N: 430 x 510 x 98mm / 16.92" x 20.08" x 3.86"